


10-16 x 1-1/2" HWH with Bonded Washer

Teks®

Buildex # 1308000



MASONPRO, Inc.
Northville, MI 48167
1-800-659-4731
www.masonpro.com

Jan 2016

Product Name: Climaseal®

Description: Climaseal is a high quality metal filled thermoset coating. Climaseal has been uniquely formulated to react and form a complete long life protection to provide the optimum in corrosion resistance properties. Climaseal is self sacrificing to the base substrate if penetrated or damaged. Fasteners coated with Climaseal exhibit excellent resistance to most forms of abrasion and torque.

Chemical Identification: Organic Metallic Polymer

Color: Silver/Metallic Grey

Cure: Thermoset

Typical Film Properties:

| | |
|---------------------|-----------|
| Humidity Resistance | Excellent |
| Solvent Resistance | Excellent |
| Impact Resistance | Excellent |
| UV Resistance | Excellent |

Fastener: TEKS / Maxiseal / SCOTS

Base Treatment: Zinc (non-electrolytically applied)

Film Climaseal - Metal filled (Aluminum)

Thermo-set Polyester

Test Method: Salt Spray, ASTM B117
1000 Hours -10% or less red rust
Kesternich, DIN50018, 2.0L
30 Cycles- 10% or less red rust

Pull-Out Data (Average Lbs. Ultimate)

| Steel Thickness | 22 ga. | 20 ga. | 18 ga. | 16 ga. | 14 ga. | 12 ga. |
|-----------------|--------|--------|--------|--------|--------|--------|
| | .030" | .036" | .048" | .060" | .075" | .105" |
| | 266 | 299 | 499 | 708 | 967 | 1474 |

Fastener Values

| Tensile | Shear Avg. Ultimate | Torsional Strength |
|-----------|---------------------|--------------------|
| 1936 lbs. | 1400 lbs. | 61 in/lbs. |

Typical Use:

Attaching Brick Veneer Anchors

Teks and Climaseal are Trade Marks of ITW Buildex And Illinois Tool Works, Inc.

BUILDING IDEAS THAT WORK®