



Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 01/04/2016 Date of issue: 08/31/2016

Version: 1.1

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply

Document Code: HSDS050

1.2. Intended Use of the Product

Use of the substance/mixture: Roofing Membrane Components

1.3. Name, Address, and Telephone of the Responsible Party

Company

HYLOAD Inc.
5020 Enterprise Parkway
Seville, Ohio 44273
(800)457-4056
www.hyload.com

1.4. Emergency Telephone Number

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

GHS-US classification

Comb. Dust

2.2. Label Elements

GHS-US Labeling

Signal Word (GHS-US) : Warning

Hazard Statements (GHS-US) : May form combustible dust concentrations in air when processed.

2.3. Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. When heated to decomposition, emits toxic fumes. Contains chemicals with hazards that are associated with their dust and usual forms. The hazards associated with these chemicals are not bioavailable under normal conditions of use due to the compounds being polymer bound.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product Identifier | % |
|--|----------------------|-----------------|
| Polyvinyl chloride | (CAS No) 9002-86-2 | 34.39 - 35.8 |
| Polymer | (CAS No) Proprietary | 34.39 - 35.8 |
| Filler | (CAS No) Proprietary | 14.85 - 23.81 |
| Silica, amorphous | (CAS No) 7631-86-9 | <= 11.5 |
| Chlorinated paraffin waxes and hydrocarbon waxes | (CAS No) 63449-39-8 | 4.75 - 4.83 |
| Calcium hydroxide | (CAS No) 1305-62-0 | <= 1.25 |
| Bisphenol A | (CAS No) 80-05-7 | <= 1.25 |
| Carbon black | (CAS No) 1333-86-4 | 0 - 0.79 |
| 2-Hydroxy-4-n-octoxybenzophenone | (CAS No) 1843-05-6 | 0.5 - 0.58 |
| Titanium dioxide | (CAS No) 13463-67-7 | <= 0.5 |
| Quartz | (CAS No) 14808-60-7 | 0.198 - 0.28572 |

Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if pain, blinking or redness persist.

First-aid Measures After Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: May cause an allergic reaction in sensitive individuals.

Symptoms/Injuries After Inhalation: If processed, prolonged inhalation of dust may cause respiratory irritation. When heated, material emits irritating fumes.

Symptoms/Injuries After Skin Contact: Under normal conditions of use may cause slight mechanical irritation. Dust particles generated from processing may cause an allergic reaction in sensitive individuals.

Symptoms/Injuries After Eye Contact: Dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Prolonged inhalation of fumes from thermal decomposition may have long-term adverse effects.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide, alcohol-resistant foam, dry chemical.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Dust generated from processing may present a dust explosion hazard.

Explosion Hazard: Dust explosion hazard in air when processed.

Reactivity: Hazardous reactions will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other Information: Risk of dust explosion when processed.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid prolonged contact with eyes, skin and clothing. Do not breathe fumes from fires or vapors from decomposition. Avoid breathing dust. Avoid generating dust. Remove ignition sources. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Sweep or vacuum the product to recover it.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. For particulates and dust: Use explosion proof vacuum during cleanup, with appropriate filter. Do not mix with other materials. Vacuum clean-up is preferred. If sweeping is required use a dust suppressant. Use only non-sparking tools.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Accumulation and dispersion of dust with an ignition source can cause a combustible dust explosion. Keep dust levels to a minimum and follow applicable regulations.

Precautions for Safe Handling: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Do not breathe dust or fumes. Avoid creating or spreading dust. Keep away from heat, sparks, open flames, hot surfaces. – No smoking.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. If dust is generated: Use explosion-proof electrical, ventilating, lighting equipment. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Products: Strong acids, strong bases, strong oxidizers.

7.3. Specific End Use(s)

Roofing Membrane Components

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

| Filler | | |
|-------------------------------|--------------------------------------|--|
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust) |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| Quartz (14808-60-7) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 0.025 mg/m ³ (respirable fraction) |
| USA ACGIH | ACGIH chemical category | A2 - Suspected Human Carcinogen |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 0.05 mg/m ³ (respirable dust) |
| USA IDLH | US IDLH (mg/m ³) | 50 mg/m ³ (respirable dust) |
| USA OSHA | OSHA PEL (STEL) (mg/m ³) | 250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2 |
| Titanium dioxide (13463-67-7) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 10 mg/m ³ |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |
| USA IDLH | US IDLH (mg/m ³) | 5000 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ (total dust) |
| Calcium hydroxide (1305-62-0) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 5 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 5 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) |
| Silica, amorphous (7631-86-9) | | |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 6 mg/m ³ |
| USA IDLH | US IDLH (mg/m ³) | 3000 mg/m ³ |

Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | | |
|---------------------------------------|--------------------------------------|---|
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 6 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 20 mppcf (80mg/m ³ /%SiO ₂) |
| Carbon black (1333-86-4) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 3 mg/m ³ (inhalable fraction) |
| USA ACGIH | ACGIH chemical category | Confirmed Animal Carcinogen with Unknown Relevance to Humans |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 3.5 mg/m ³ 0.1 mg/m ³ (Carbon black in presence of Polycyclic aromatic hydrocarbons) |
| USA IDLH | US IDLH (mg/m ³) | 1750 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 3.5 mg/m ³ |
| Polyvinyl chloride (9002-86-2) | | |
| USA ACGIH | ACGIH TWA (mg/m ³) | 1 mg/m ³ (respirable fraction) |
| USA ACGIH | ACGIH chemical category | Not Classifiable as a Human Carcinogen |

8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. If dust is generated: Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

Hand Protection

: Chemically resistant materials and fabrics.

Eye Protection

: Wear protective gloves.

Skin and Body Protection

: Chemical goggles or safety glasses.

Respiratory Protection

: Wear suitable protective clothing.

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State

: Solid

Appearance

: Gray, black, or white

Odor

: No data available

Odor Threshold

: No data available

pH

: No data available

Evaporation Rate

: No data available

Melting Point

: No data available

Freezing Point

: No data available

Boiling Point

: No data available

Flash Point

: No data available

Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--|---------------------|
| Auto-ignition Temperature | : No data available |
| Decomposition Temperature | : No data available |
| Flammability (solid, gas) | : No data available |
| Vapor Pressure | : No data available |
| Relative Vapor Density at 20 °C | : No data available |
| Relative Density | : No data available |
| Solubility | : No data available |
| Partition Coefficient: N-Octanol/Water | : No data available |
| Viscosity | : No data available |

9.2. Other Information No additional information available.

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials. Sparks, heat, open flame and other sources of ignition.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition generates: Carbon oxides (CO, CO₂). Nitrogen oxides. Metal oxides. Hydrogen chloride. Benzene. Phosgene. Organic acids. Formaldehyde. Acrolein. Low molecular weight hydrocarbon fragments.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

| | |
|--|----------------------------------|
| 2-Hydroxy-4-n-octoxybenzophenone (1843-05-6) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rabbit | > 10 g/kg |
| Quartz (14808-60-7) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rat | > 5000 mg/kg |
| Titanium dioxide (13463-67-7) | |
| LD50 Oral Rat | > 10000 mg/kg |
| Calcium hydroxide (1305-62-0) | |
| LD50 Oral Rat | 7340 mg/kg |
| Bisphenol A (80-05-7) | |
| LD50 Oral Rat | 3300 mg/kg |
| LD50 Dermal Rabbit | 3 ml/kg |
| LC50 Inhalation Rat | > 0.17 mg/l (Exposure time: 6 h) |
| Silica, amorphous (7631-86-9) | |
| LD50 Oral Rat | > 5000 mg/kg |
| LD50 Dermal Rabbit | > 2000 mg/kg |
| LC50 Inhalation Rat | > 2.2 mg/l (Exposure time: 1 h) |
| Carbon black (1333-86-4) | |
| LD50 Oral Rat | > 8000 mg/kg |
| Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8) | |
| LD50 Oral Rat | > 21500 µl/kg |

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

| | |
|--|---|
| Quartz (14808-60-7) | |
| IARC group | 1 |
| National Toxicology Program (NTP) Status | Known Human Carcinogens. |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| Titanium dioxide (13463-67-7) | |
| IARC group | 2B |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| Silica, amorphous (7631-86-9) | |
| IARC group | 3 |
| Carbon black (1333-86-4) | |
| IARC group | 2B |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |
| Polyvinyl chloride (9002-86-2) | |
| IARC group | 3 |
| Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8) | |
| IARC group | 2B |
| OSHA Hazard Communication Carcinogen List | In OSHA Hazard Communication Carcinogen list. |

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: If processed, prolonged inhalation of dust may cause respiratory irritation. When heated, material emits irritating fumes.

Symptoms/Injuries After Skin Contact: Under normal conditions of use may cause slight mechanical irritation. Dust particles generated from processing may cause an allergic reaction in sensitive individuals.

Symptoms/Injuries After Eye Contact: Dusts caused from milling and physical alteration will likely cause eye irritation. Fumes from thermal decomposition or molten material will likely be irritating to the eyes.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: Prolonged inhalation of fumes from thermal decomposition may have long-term adverse effects.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General : Not classified.

| | |
|---|--|
| 2-Hydroxy-4-n-octoxybenzophenone (1843-05-6) | |
| LC50 Fish 1 | > 100 mg/l (Exposure time: 96 h - Species: Brachydanio rerio) |
| Calcium hydroxide (1305-62-0) | |
| LC50 Fish 1 | 50.6 mg/l |
| Bisphenol A (80-05-7) | |
| LC50 Fish 1 | 3.6 (3.6 - 5.4) mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| EC50 Daphnia 1 | 10.2 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC 50 Fish 2 | 4.0 - 5.5 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| EC50 Daphnia 2 | 3.9 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| Silica, amorphous (7631-86-9) | |
| LC50 Fish 1 | 5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static]) |
| EC50 Daphnia 1 | 7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia) |
| Carbon black (1333-86-4) | |
| EC50 Daphnia 1 | 5600 mg/l (Exposure time: 24 h - Species: Daphnia magna) |

Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|--|---|
| Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8) | |
| LC50 Fish 1 | > 300 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| LC 50 Fish 2 | > 0.0109 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through]) |

12.2. Persistence and Degradability

| | |
|---|------------------|
| Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply | |
| Persistence and Degradability | Not established. |

12.3. Bioaccumulative Potential

| | |
|---|------------------|
| Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply | |
| Bioaccumulative Potential | Not established. |

| | |
|---|-----|
| 2-Hydroxy-4-n-octoxybenzophenone (1843-05-6) | |
| Log Pow | > 6 |

| | |
|--------------------------------------|----------------------|
| Calcium hydroxide (1305-62-0) | |
| BCF fish 1 | (no bioaccumulation) |

| | |
|------------------------------|------------|
| Bisphenol A (80-05-7) | |
| BCF fish 1 | 5.1 - 13.8 |
| Log Pow | 2.2 |

| | |
|--------------------------------------|-------------------------------|
| Silica, amorphous (7631-86-9) | |
| BCF fish 1 | (no bioaccumulation expected) |

| | |
|--|-----|
| Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8) | |
| Log Pow | > 6 |

12.4. Mobility in Soil No additional information available.

12.5. Other Adverse Effects

Other Information : Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, and international regulations.

Additional Information: Container may remain hazardous when empty. Continue to observe all precautions.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT Not regulated for transport.

14.2. In Accordance with IMDG Not regulated for transport.

14.3. In Accordance with IATA Not regulated for transport.

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

| | |
|---|--|
| 2-Hydroxy-4-n-octoxybenzophenone (1843-05-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|---|--|
| Filler | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|---|--|
| Quartz (14808-60-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|--|--|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Delayed (chronic) health hazard |
|--|--|

| | |
|---|--|
| Titanium dioxide (13463-67-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

| | |
|--|---------------------------------|
| SARA Section 311/312 Hazard Classes | Delayed (chronic) health hazard |
|--|---------------------------------|

Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| | |
|---|--|
| Calcium hydroxide (1305-62-0) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard |
| Bisphenol A (80-05-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Subject to reporting requirements of United States SARA Section 313 | |
| EPA TSCA Regulatory Flag | T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. |
| SARA Section 313 - Emission Reporting | 1.0 % |
| Silica, amorphous (7631-86-9) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Carbon black (1333-86-4) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Polyvinyl chloride (9002-86-2) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

15.2 US State Regulations

| | |
|--|--|
| Quartz (14808-60-7) | |
| U.S. - California - Proposition 65 - Carcinogens List | WARNING: This product contains chemicals known to the State of California to cause cancer. |
| Titanium dioxide (13463-67-7) | |
| U.S. - California - Proposition 65 - Carcinogens List | WARNING: This product contains chemicals known to the State of California to cause cancer. |
| Bisphenol A (80-05-7) | |
| U.S. - California - Proposition 65 - Reproductive Toxicity - Female | WARNING: This product contains chemicals known to the State of California to cause (Female) reproductive harm. |
| Carbon black (1333-86-4) | |
| U.S. - California - Proposition 65 - Carcinogens List | WARNING: This product contains chemicals known to the State of California to cause cancer. |
| Filler | |
| U.S. - Massachusetts - Right To Know List | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | |
| U.S. - Pennsylvania - RTK (Right to Know) List | |
| Quartz (14808-60-7) | |
| U.S. - Massachusetts - Right To Know List | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | |
| U.S. - Pennsylvania - RTK (Right to Know) List | |
| Titanium dioxide (13463-67-7) | |
| U.S. - Massachusetts - Right To Know List | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | |
| U.S. - Pennsylvania - RTK (Right to Know) List | |
| Calcium hydroxide (1305-62-0) | |
| U.S. - Massachusetts - Right To Know List | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | |
| U.S. - Pennsylvania - RTK (Right to Know) List | |
| Bisphenol A (80-05-7) | |
| U.S. - Massachusetts - Right To Know List | |
| U.S. - New Jersey - Right to Know Hazardous Substance List | |
| U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List | |

Hyload Flashing membranes, Hyload Surface Adhered Flashing membranes, Hyload Surface Adhered w/ drip edge Flashing membranes, ALPROOF, ALPSAM, ALPSAM WS, White Kwik Ply

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| |
|---|
| U.S. - Pennsylvania - RTK (Right to Know) List |
| Silica, amorphous (7631-86-9) |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List |
| Carbon black (1333-86-4) |
| U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances U.S. - Pennsylvania - RTK (Right to Know) List |
| Polyvinyl chloride (9002-86-2) |
| U.S. - New Jersey - Right to Know Hazardous Substance List |
| Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8) |
| U.S. - Massachusetts - Right To Know List |

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 01/04/2016
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

| | |
|------------|---|
| Comb. Dust | May form combustible dust concentrations in air |
|------------|---|

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

SDS US (GHS HazCom)