


# PRODUCT SUBMITTAL


WIRE-BOND

## SureTie WS Tapcon **Thermal\*** (Wood Framing)



\* "Sure-Tie fasteners do not promote thermal bridging."

ASTM Certified: \*Test Results Available Upon Request

| MATERIAL CONFORMANCE   | SIZES / FINISHES   |        |        |        |    |        |    |        |    |        |  |    |    |    |
|--|--|--------|--------|--------|----|--------|----|--------|----|--------|--|----|----|----|
| <p><b>ASTM A1064 / A1064M, A82 / A82M</b> - (Cold drawn steel wire)<br/>Tensile Strength - 80,000 psi<br/>Yield Point - 70,000 psi</p> <p><b>ACI / ASCE 530</b> - (Building code requirements for masonry structures)</p> <p>Hot Dip Galvanized after fabrication / Zinc Coating<br/><b>ASTM A153 / A153M-B2 (1.50 oz per sq ft)</b></p> <p>Stainless Steel <b>ASTM 580 / ASTM 580M Type 304</b> (Type 316 available on special order)</p> | <p><b>#4532 SureTie WS Tapcon</b><br/>Blue climaseal finish resulted in 0% red rust at 1000 hours exposure to ASTM B-117 salt spray testing.</p> <p><b>Insulation:</b></p> <table border="0"> <tr> <td>0"</td> <td>1"</td> <td>1-1/2"</td> <td>2"</td> <td>2-1/2"</td> </tr> <tr> <td>3"</td> <td>3-1/2"</td> <td>4"</td> <td>4-1/2"</td> <td></td> </tr> </table> <p><b>#4515 SureTie WS Double Hook</b></p> <table border="0"> <tr> <td>3"</td> <td>4"</td> <td>5"</td> </tr> </table> | 0"     | 1"     | 1-1/2" | 2" | 2-1/2" | 3" | 3-1/2" | 4" | 4-1/2" |  | 3" | 4" | 5" |
| 0"   | 1"   | 1-1/2" | 2"     | 2-1/2" |    |        |    |        |    |        |  |    |    |    |
| 3"   | 3-1/2"   | 4"     | 4-1/2" |        |    |        |    |        |    |        |  |    |    |    |
| 3"   | 4"   | 5"     |        |        |    |        |    |        |    |        |  |    |    |    |
| <p> <b>Recycled Content:</b><br/>Mill Galvanized &amp; Hot Dipped,<br/>82.8% Post-Consumer<br/>17% Post Industrial / Pre-Consumer,</p> <p>Stainless Steel,<br/>60% Post Consumer<br/>V O C Content - 0%</p>   | <p><b>FINISH : ( SureTie WS Double Hook)</b></p> <p>Hot Dip Galvanized<br/>Stainless Steel</p>   |        |        |        |    |        |    |        |    |        |  |    |    |    |

WIRE-BOND

MASONPRO, Inc.  
43300 Seven Mile Road  
Northville, MI 48167  
1-800-659-4731  
www.masonpro.com